

INTRODUCTION

DESCRIPTION

Colourless solution based on a mixture of weak acids, ready for use to dissolve salts and limescale. Always rinse with clean water.

USES

For inside and outside use.

Removal of salts on a mineral substrate.

Removal of limescale on a mineral substrate.

ADVANTAGES

- Easy application
- Mixture of weak acids = limited risk
- Volatile

TECHNICAL SPECIFICATION

IDENTIFICATION DATA	
State	Liquid
Appearance	Water
Colour	Colourless
Odour	Characteristic
Density NBN EN 1015-10	1014 kg/m ³
Apparent density (at 20°C)	1.014 kg/L
Packaging	5L cans 1L bottles
Storage	6 months in a dry spot, sheltered from frost, not in contact with the ground and in the original unopened packaging. Never leave the products in full sunlight.
Customs classification	28 11 19 80
ADR classification	"UN 2790 ACETIC ACID SOLUTION, 8, III, (E)"
APPLICATION DATA	
Consumption	100 to 150ml/m ² /pass
Application temperature	+5°C min to +30°C max
Relative humidity	65% min and 90% max Bar the use of appliances which are capable of drying out the humidity of the air (dehumidifier, air conditioner, etc.) 1 week before and after the site, as well as during application.
Humidity of the substrate	Water soaked but looking matt, not trickling

APPLICATION

SUBSTRATE AND PREPARATION

The substrate must be sound, clean, free from grease and water soaked but looking matt, not trickling.

Remove any part that is not adhering or cohesion is weak.

Remove dust carefully.

There must not be any stagnant water in the surface at the time of application.

Consult the legal notice at the end of the document

Page n°1 - This technical sheet comprises 2 page(s) - Edition NF 1/09/15 - This version supersedes all previous versions.

PREPARATION OF THE MIXTURE

DISSEL A15 is applied as it is or diluted by 10 to 50% clean water, dependent on the tasks and the substrate.

USE

Dampen the substrate thoroughly to make the water "mat".

Apply DISSEL A15 with a brush or a paintbrush.

Leave to act for 1 minute.

Brush vigorously.

Rinse with clean water.

Repeat the operation if necessary.

MISCELLANEOUS

CLEANING TOOLS

Clean the product off while still fresh with water.

WARNINGS

Sites must be protected against rain, sun, wind and frost until drying is complete and/or until immersion in water is complete.

ADVICE

Follow the application instructions exactly, according to the purpose of the product. Never use products other than those shown in this technical data sheet, to avoid any risk of things going wrong.

For a single site and for each product type, always use products bearing the same batch number.

ENVIRONMENT

Remove waste to a specialist collection centre.

SAFETY

Solution based on weak acids. Keep out of reach of children. Avoid contact with the skin and the eyes. If it comes into contact with the eyes or skin, wash immediately in copious quantities of water and consult a specialist.

Consult the safety data sheet available on request or at www.beal.be

LEGAL NOTICE

These instructions, and , in particular, the recommendations for the application and final use of the products, are provided in good faith and are based on the knowledge and experience that the BEAL Corporation has acquired to date about its products when they have been properly stored, handled and applied under normal conditions. In practice, the differences between materials, substrates and specific conditions on site are such that this information or any written recommendation or advice given do not imply any guarantee of merchantable quality other than the statutory guarantee against hidden defects. Our liability cannot be committed in any way, assuming an application not compliant with our teaching. None of the data and information relating to suitability and application absolve the client from the need to carry out its own verifications and tests. All orders are accepted subject to our current terms and conditions of trading. It is essential that users consult the most recent version of the instructions for the product in question. These will be delivered to them on request.

Consult the legal notice at the end of the document

Page n°2 - This technical sheet comprises 2 page(s) - Edition NF 1/09/15 - This version supersedes all previous versions.