

PRESENTATION

DESCRIPTION

Acrylic resin in water emulsion, colorless. **RESIPACT** is a liquid fixative with a milky consistency and appearance, designed for old, uncertain, or new absorbent substrates.

AREAS OF APPLICATION

Indoor and outdoor use.

Hardening fixative for porous and absorbent substrates (renders, coatings, plaster, clay-limestone masonry, terracotta, fiber cement, concrete, aerated concrete, mortars, old paints with very good adhesion).

Also acts as a dust suppressant for powdery bricks (nitrate-free).

Hardens almost all powdery substrates. Very effective in neutralizing chimney soot stains (contact us for specific use).

Applications are very flexible and temporarily prevent the penetration of driving rain and runoff without a finishing coat. They are microporous and practically non-saponifiable.

ADVANTAGES

- Odorless and non-toxic
- Easy to use
- Fast drying
- Helps eliminate substrate porosity, blocks absorbent and sandy surfaces
- Provides exceptional adhesion for finishing coats

TECHNICAL SPECIFICATION

IDENTIFICATION DATA	
State	Liquid
Appearance	Milky
Color	Whitish / Milky
Odor	Characteristic
Apparent Density (at 20°C)	1.000 kg/l
Packaging	1 L bottles, 5 L cans
Storage	6 months in a dry place, protected from frost, and off the ground in original sealed packaging. Never expose products to direct sunlight.
Customs Classification	39 09 50 90
APPLICATION INFORMATION	
Consumption	200 ml/m ² depending on substrate porosity
Application Temperature	+5°C min. to +30°C max.
Air Humidity	65% min. to 90% max. Avoid using devices that dry the air (dehumidifiers, air conditioning, etc.) one week before, during, and after application.
Substrate Humidity	< 3%
Drying Time (at 20°C)	Touch dry: 1 h / Fully dry: 4 h

APPLICATION

SUBSTRATE AND PREPARATION

The substrate must be sound, dry before and after application, clean, matte, and grease-free. It must be hard, non-friable, and non-powdery.

Remove any non-adherent or weakly cohesive parts and any substances that may impair adhesion.

Thoroughly dust off.

Refer to the legal information at the end of the document

MIXTURE PREPARATION

RESIPACT is ready to use and should be applied as is. Do not dilute.

APPLICATION

Apply RESIPACT with a brush or spray gun (conventional or airless).

For normal application, one coat is sufficient. For highly absorbent and sandy substrates, apply multiple coats to ensure uniform surface hardness.

Apply "wet-on-wet".

MISCELLANEOUS**CLEANING TOOLS**

If product is fresh, clean with water.

WARNINGS

Our products are sensitive to humidity, frost and heat. Always store them in a dry place, away from frost and without contact with the ground

When applying RESIPACT indoors, ensure normal ventilation.

Do not apply on substrates containing salts (sodium sulfate, nitrates, calcium, etc.).

Do not apply if the substrate is damp., in the closed original packaging. Never leave products in direct sunlight.

ADVICE

Strictly follow the application protocols according to the intended use of the product. Never use products other than those specified in this technical data sheet to avoid any risk of incompatibility or failure.

For the same project and product type, always use materials with the same batch number. Make sure to use only original, unopened bags.

Always carry out preliminary tests. In case of doubt, please contact us.

ENVIRONMENT

Dispose of in a specialized waste collection center.

SAFETY

Protect skin and eyes. In case of contact with eyes or open wounds, rinse immediately and thoroughly with clean water.

If problems occur, consult a specialist.

The safety data sheet is available on request or at www.bealinternational.com

LEGAL INFORMATION

The technical instructions and in particular the recommendations about how to apply and use the products are provided in good faith and are based on the current knowledge and experience acquired by BEAL about its products when they are properly stored, handled and applied under normal conditions. In practice, variations in the various materials, substrates and specific conditions encountered on site are such that adhering to this information or to any written recommendation or advice given does not deliver any guarantee of marketable quality other than the statutory guarantee against hidden defects. We accept no liability should the customer fail to adhere to our instructions or recommendations when applying a product. None of the data and information provided relating to the use and application of our product releases customers from the requirement to conduct their own checks and tests. All orders are accepted subject to our current general terms and conditions of business. It is essential that users read the most recent version of the instructions for the product in question, which will be sent to them on request.

Refer to the legal information at the end of the document

Page n°2 - This technical document contains 2 page(s) - Edition AG 2025-10-06 - This edition cancels and replaces all previous editions.

BEAL INTERNATIONAL S.A.

Z.I. NOVILLE-LES-BOIS • RUE DU TRONQUOY 8 • 5380 FERNELMONT • BELGIUM
T. +32 (0) 81 83 57 57 • F. + 32 (0)81 83 57 67 • RPM NAMUR • TVA BE 0414 592 153
INFO@BEAL.BE • WWW.BEAL.BE

