



HOW TO TAKE CARE OF MORTEX[®]

Although waterproof in the mass and hardwearing, **MORTEX[®] coating must be protected against stains**, just like a natural stone.

The maintenance of a surface coated with MORTEX[®] coating depends mainly on the protection applied thereto.

For surfaces varnished with BIPUR, it is best to use a neutral cleaner.

Regarding surfaces protected with natural products like oil (OIL MORTEX[®]) or wax (BEALWAX), those are more sensitive to acids and fats. In everyday life, a sponge or cloth with mild & nourishing soap (without mordant agents) is sufficient, for example a solution of 1 liter of lukewarm water with 1 to 2 spoons of FINISH SA TR well diluted (available at BEAL or its distributors).

Moreover, it is advisable **to treat regularly those surfaces with oil (OIL MORTEX[®]) or wax (BEALWAX)** as applicable, in order to « feed » the underground. Impregnate slightly the surface to treat using a cloth, paintbrush or roller. Collect up any surplus with nontinted absorbent paper and spread the remainder immediately with a scrap of clean white cotton fabric. This is to avoid drips on vertical surfaces or extra thickness on horizontal surfaces. Take care to remove any limescale or other residue beforehand.

In a shower, whatever the coating, limescale contained in water lays down on it after each use, allowing various residues (soap, dirt...) to hang onto it. **Weekly maintenance is thus needed.** For the removal of such residues on MORTEX® coating, use white vinegar (also called crystal vinegar) diluted in lukewarm water (1 part vinegar for 2 parts water). Spray and leave for a few moments before wiping with a soft sponge. Start with small concentrations of vinegar and increase according to the quantity of limescale (maximum 2 parts vinegar for 1 part water). This also applies to the plumbing fittings in contact with MORTEX® coating. **We recommend that you always do a test on a small area beforehand.**



LEGAL NOTICE

These instructions, and, in particular, the recommendations for the application and final use of the products, are provided in good faith and are based on the knowledge and experience that the BEAL Corporation has acquired to date about its products when they have been properly stored, handled and applied under normal conditions. In practice, the differences between materials, substrates and specific conditions on site are such that this information or any written recommendation or advice given do not imply any guarantee of merchantable quality other than the statutory guarantee against hidden defects. Our liability cannot be committed in any way, assuming an application not compliant with our teaching. None of the data and information relating to suitability and application absolve the client from the need to carry out its own verifications and tests. All orders are accepted subject to our current terms and conditions of trading. It is essential that users consult the most recent version of the instructions for the product in question. These will be delivered to them on request.

Beal International s.a.
Rue du Tronquoy 8 | 5380 Fernelmont | BELGIUM
Tel.: +32 (0) 81 83 57 57 | Fax: +32 (0) 81 83 57 67
info@beal.be - www.bealinternational.com
VAT: BE 0414 592 153

